FESTFLOOR

INSTRUCTIONS FOR USE OF FESTFLOOR MICROCEMENT DECORATIVE COATINGS

Festfloor microcement coatings are a decorative finish for floors, walls and stairs. They are applied by hand, which makes them a unique handcrafted finish. Coatings made using the Festfloor Life, FestWall, Festfloor Go!, HydroFest and Festfloor Titan systems are characterized by the discolorations, "burn marks" and so-called clouding typical of microcement coatings. Festfloor coatings are approx. 2 - 3 mm thick and reproduce the shape of the substrate (floors, walls, stairs).

RULES TO FOLLOW DURING USE:

- For 24 hours after applying the sealer, do not walk on the finished floor (restrict access).
- After 24 hours from applying the sealer, light foot traffic is allowed.
- For 3 months after applying the sealer, do not cover the surface for more than 24h at a time to ensure proper drying of the sealer. Covering may cause permanent discoloration.
- After 14 days from applying the sealer, the coating may be used in accordance with its intended purpose, however avoiding moving heavy objects (e.g. furniture) across it, avoiding dropping heavy, hard objects with sharp edges onto the coating, and avoiding intensive use of high-heeled shoes.
- Festfloor coatings should be used in a similar way to a high-quality parquet floor. During use, avoid dropping hard and sharp objects onto the finished coating.
- Protect the legs of chairs and furniture with felt pads to ensure even load distribution and limit the formation of indentations. We do not recommend using metal furniture casters. Rubber ones will be safe, for example.
- The coatings should be cleaned regularly with FEST Cleaner, POWER-FEST, FEST Calc or mild household detergents (before using a new product, we recommend testing it in an inconspicuous area). Please do not use corrosive agents, harsh scouring pads or magic sponges (there is a risk of damaging the sealer).
- Do not leave spilled water or other liquids on the surface for too long, and remove any dirt as it appears so that it does not penetrate into the sealer structure.
- Leaving water or other spilled liquids without the possibility of evaporation may permanently damage the structure of the microcement surface.
- Tyres and other rubber products may leave a permanent yellow residue on the microcement surface, so it is not recommended to leave them on the finished surface for long periods of time.
- Periodically (depending on the intensity of use), after washing and drying the floor, use a mop or cotton cloth to apply FEST Wax or FF WAX CARE maintenance wax, available from the contractor or the manufacturer.
- The usage guidelines given apply under the following conditions: 22ºC and 50% humidity. Lower temperature and higher humidity may extend the drying time of the products.